

# RGHK4

## THE TWIN LEG SCAFFOLDER'S KIT RGHK4

The twin leg version of our Scaffolder's Kit contains a two point safety harness and a twin leg fall arrest lanyard.

The addition of a twin leg lanyard means workers can safely and efficiently move between anchor points, whilst working close to an open edge. This version comes with two scaffold hooks meaning it is ideal for clipping to scaffolding or other steel structures.

### Kit contains

- / Front & rear D harness (RGH2)
- / Twin leg webbing lanyard and shock absorber (RGL3)
- / 17mm steel screwgate karabiner (RGK1)
- / 60mm aluminium double-action scaffold hook with captive eye x 2 (RGK11)

EN 362:2004

EN 361:2002

EN 355:2002



\* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*

RIDGEGEAR LIMITED

Nelson Street, Leek, Staffordshire, ST13 6BB

+44 (0)1538 384 108

sales@ridgegear.com

ridgegear.com

## ITEM SPECIFICATIONS

### RGHK4

#### FRONT & REAR D HARNESS

##### RGH2

/ Front & rear attachment point

EN 361:2002

Web material: 45mm RIDGE Protect anti-bacterial polyester\*

Fittings: High tensile steel alloy

Weight: 1.1kg

#### TWIN LEG WEBBING LANYARD AND SHOCK ABSORBER

##### RGL3

EN 355:2002

Web material: 26mm RIDGE Protect anti-bacterial polyester\*

Fittings: 17mm steel screwgate karabiner (RGK1)  
60mm aluminium double-action scaffold hook with captive eye (RGK11)

Max arrest force: <6kN

Length(s) 1.4m (up to 140kg user)  
1.8m (up to 100kg user) (including connectors)

#### 17MM STEEL SCREWGATE KARABINER

##### RGK1

EN 362:2004

Material: Steel

Plating: Zinc

Gate opening: 17mm

External length: 107mm

Closure type: Screwgate

MBS: 23kN

Weight: 160g



#### 60MM ALUMINIUM DOUBLE-ACTION SCAFFOLD HOOK WITH CAPTIVE EYE

##### RGK11

EN 362:2004

Material: Aluminium

Plating: Anodised

Gate opening: 60mm

Eye diameter: 30mm

External length: 248mm

Closure type: Double action

MBS: 23kN

Weight: 480g

